

ON-675

Power by WEICHAI

6M33D670E200

Prime power: 540KW/675KVA

Standby power: 600KW/750KVA

GENERATING POWER SOLUTIONS



Increased availability for new operations

Reliable, robust and versatile generator. Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs



The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals. Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



ONEWPOWER

WWW.ONEWPOWER.COM

DIMENSION		OPEN TYPE	SILENT TYPE
Length (L)	mm	3550	5482
Width (W)	mm	1602	1830
Height (H)	mm	2205	2500
Dry weight	kg	4443	6446
Fuel tank	L	NA	740

Technical Data

Model ON-675

Rated prime power	KW	540
Rated standard power	KW	600
Rated voltage line to line	V	380~415
Maximun sound level	dB(@7m)	≤72

Engine

Model	6M33D670E200	
Aspiration	Turbochargine and aftercooled	
Fuel system	mechanical pump	
No. cylinders	6	
Displacement	Liquid	19.6
Bore*Stroke	mm	150*185
Compression ratio	15:1	
Rated speed	r/min	1500
Rated net power(with fan)	Kw	540
Governor type	Electronic	

Exhaust system

Exhaust gas flow	4021.9kg/h	
Exhaust gas temp	° F (° C)	<750
Max back pressure	7.5Kpa	

Aspiration system

Max inlet pressure	kPa	≤3.5
Combustion volume	L/s	/
Air flow	kg/h	3878.3

Fuel system

100% load(Prime power)	L/h	150
75% load(Prime power)	L/h	111.5
50% load(Prime power)	L/h	75.8
Fuel tank capacity	L	740

Lubrication system

Oil capacity	L	61
Oil consumption	L/H	150
Oil pressure	kPa	10
(continuous operation)		

Cooling system

Coolant capacity	L	43.93
Thermostat operation range	°C	76-88
Max water temperature	°C	98

Alternator

Model	ON-675	
Phase	3	
Voltage	V	380~415
Bearing	1	
Power factor	0.8	
Frequency	Hz	50
Prime power	KW	540
Exciter Type	Brushless, self-excitation	
Voltage regulation	%	±0.5
Protection Grade	IP 23	
Insulation grade	H/H	
Altitude	m	≤1000

Controller

- Model
- Protective functions:
- Low oil pressure
 - High water temperature
 - High/low voltage
 - High Engine Temperature and Overspeed.
 - Voltage regulator frequency regulator
 - Emergency stop
 - Start failure



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

Standard features

- Engine
- Radiator 50°C max, fans are driven by belt
- 24V charge alternator
- Alternator: single bearing alternator IP23, insulation class H/H
- Standard auto control system
- One set of air filter, fuel filter, oil filter
- Main line circuit breaker/MCCB
- Base fuel tank
- Two 24V batteries, rac and cable
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)
- User manual

Options

- Battery charge
- Engine heater
- Alternator heater
- PMG
- Water oil separator
- Daily fuel tank
- Remote control panel
- Automatic transfer switch/ATS
- Switch box
- Standard: ● Options: ○

Warranty



WEICHAI ENGINE

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours (whichever occurs first).

Dimensions



ONEWPOWER

ADD: NO . 1 0 7 XIYUAN ROAD , JINAN DISTRICT, FUZHOU CITY, FUJIAN, CHINA

Phone: 15980204507 E-mail: jina@onewpower.com

WWW.ONEWPOWER.COM

